

2567E, F, G & H TYPES OF DISC REPRODUCER

INTRODUCTION

The Westrex 2567 Type is a sophisticated and dependable 4-speed Disc Reproducer available in monophonic or stereophonic/monophonic form.

TYPES

- (1) 2567 E provides 4 speeds and a monophonic output. It is for operation from a 240 V, single-phase 50 HZS supply.
- (2) 2567 F provides 4 speeds and a stereophonic/monophonic output. It is for operation from a 240 V, single-phase 50 HZS supply.
- (3) 2567 G provides 4 speeds and a monophonic output. It is for operation from a 110V, single-phase 60 HZS supply.
- (4) 2567 H provides 4 speeds and stereophonic/monophonic output. It is for operation from a 110V, single-phase 60 HZS supply.



MAIN FEATURES

The 2567 mono/stereo, 4 speed Transcription Disc Reproducer has design features which include plug-in transistor pre-amplifiers, volume control, separate treble and bass tone controls, and power supply unit.

SPECIAL POINTS

1. The 4 speed transcription turntable is by Goldring Lenco (Model GL 70).
2. The light-weight, high-quality pick-up arm incorporates a device for raising and lowering the pick-up and for locating the start of the groove.
3. The set contains its own monophonic/stereophonic pre-amplifiers, with separate high-frequency and low-frequency tone controls and a numbered master volume control.
4. The transistorised pre-amplifiers are designed as plug-in modules.
5. The diamond/sapphire styli in the cartridge are of measured quality and give characteristics commensurate with Westrex's high standards of reproduction. An alternative cartridge can be supplied if a strong preference is expressed for a particular type from which the high performance can be maintained.
6. The operational output from each amplifier is in the order of -10 DBM to 0 DBM into a 600 ohm line. This is more than adequate to modulate fully the Westrex power amplifier system to provide spectacular sound reproduction through the Westrex 5010 or 5013 Auditorium Loudspeaker System.

SPECIAL POINTS continued

7. The reproducing deck with amplifiers and power unit is mounted in a robust teak-sided cabinet with a transparent Perspex lid, presenting an attractive appearance as well as giving adequate protection to the essential reproducing units.

DIMENSIONS AND WEIGHTS (Approx.)

Width	17¼ ins.	(43.8 cms.)
Depth	18 1/8 ins.	(46.0 cms.)
Height (over lid)	8½ ins.	(21.6 cms.)
Weight	20 lbs.	(9.1 kgms.)

NOTE. The Westrex 5000 Series of cinema projection and sound equipments are British made throughout. The Westrex Installation Planning Department is freely available to give advice on any aspect of film presentation.